


MPC103-845

10.1" WXGA TFT Fanless Medical Grade Touch Panel Computer with Intel® Celeron® Processor N3060



1. Power LED
2. HDD LED
3. Brightness adjust +/-
4. Display on/off
5. Volume adjust
6. Mic-in (optional)



1. Power switch (ATX)
2. Terminal block for DC power input
3. Screw connector with AC power adapter
4. 2 x USB 2.0
5. Audio (Line-out)
6. 1 x RS-232/422/485
7. 1 x RS-232
8. 2 x USB 3.0
9. 2 x LAN
10. AT/ATX switch

Features

- 10.1" WXGA TFT LCD display with LED backlight
- Fanless design with Intel® Celeron® processor N3060
- 2 GbE LANs, 4 USB and 2 COM
- Plastic and IP65-rated front bezel
- Supports RFID (optional)
- External AT/ATX mode selection switch
- Easy access storage design
- Supports panel mount, wall mount, VESA arm and desktop stand
- Adjustable RS-232/422/485 setting via BIOS
- CE (EN 60601-1) and FCC Part 18 EN 60601-1-2 (ESD contact 8kV, air 15kV)



▲ Side view

Introduction

The MPC103-845 is a 10.1" fanless medical touch panel computer. It adopts a modern, super sleek and fanless design and has a 10.1" TFT LCD. It is powered by the Intel® Celeron® processor N3060 dual core up to 2.48 GHz. For wireless network connection, the MPC103-845 offers 2 PCI Express Mini Card slots. By just plugging in the WLAN card, customers can have instant access to wireless LAN/GPRS/GSM/4G environments. Besides, it provides two types of power input: DC power with terminal block connector and AC power adapter with screw type connector.

Super Slim & Ultra Lightweight Design

With a thickness of 38 mm and weight of 1.08 kg, the MPC103-845 is designed for use in space-constrained environments.

Certifications

This 10.1-inch medical panel platform complies with EN60601-1 ED3.1 CE, FCC Class B certifications to ensure medical operation safety.

Aluminum Back Chassis with Excellent Thermal Solution

With Axiomtek's patent for plastic plus aluminum mechanism design, the MPC103-845 can dissipate the heat easily and keep the system operation stable.

Specifications

Front Bezel	IP65, NEMA 4 rugged protection, plastic front bezel	
LCD Panel	Display Type	10.1" WXGA TFT LCD with LED backlight
	Brightness (cd/m ²)	350 nits
	Resolution	1280 x 800
	Viewing Angel (H/V)	170°/170°
Main System	CPU	Intel® Celeron® processor N3060 2 cores (up to 2.48 GHz)
	System Memory	1 x 204-pin DDR3L-1600 SO-DIMM, up to 8GB
	BIOS	AMI UEFI BIOS
	Storage	1 x Half-slim SATA SSD (only for MPC103-845-PCT-J) 1 x mSATA
	Watchdog Timer	255 levels, 0 to 255 sec.
I/O Connector	Onboard Graphics	Integrated in Intel® GFX
	1 x RS-232	
	1 x RS-232/422/485 (default RS-232)	
	1 x Switch for power on/off	
	1 x AT/ATX mode selection switch	
	2 x USB 2.0	
	2 x USB 3.0	
Expansion Interface	1 x Audio (Line-out)	
	2 x 10/100/1000 Mbps Ethernet (Intel® i211-AT)	
Touchscreen	1 x Full-size PCI Express Mini Card slot with mSATA	
	1 x Full-size PCI Express Mini Card slot with SIM	
Power Supply	Projected capacitive multi-touch	
Power Consumption	AC version: 100 to 240 VAC-DC, 65W power adapter	
	DC version: 9 to 36 VDC with over current protection fuse	
Dimension	40.32 W	
Packing Dimensions	260.8 mm (10.27") (W) x 38 mm (1.50") (D) x 194.1 mm (7.65") (H)	
Weight (net/gross)	380 mm (14.96") (W) x 100 mm (3.94") (D) x 280 mm (11.02") (H)	
Operating Temperature	1.08 kg (2.38 lb)/2.18 kg (4.8 lb)	
Relative Humidity	0°C to +40°C (+32°F to +122°F)	
Operation Vibration	20% to 90% @ +40°C; non-condensing	
Certifications	2G, 5- 500Hz, random for SSD	
	CE (EN 60601-1) and FCC Part 18 EN 60601-1-2 (ESD contact 8kV, air 15kV)	

Ordering Information

Standard

MPC103-845-J (P/N: E228103100)	10.1" WXGA fanless medical touch panel computer with Intel® Celeron® processor N3060, projected capacitive touch screen, AC-DC 65W power adapter (screw type connector) and EMI class B
MPC103-845-DC (P/N: E228103101)	10.1" WXGA fanless medical touch panel computer with Intel® Celeron® processor N3060, projected capacitive touch screen and DC power input (terminal block connector)

* Other configuration by request

* Specification and certifications may vary based on different requirements

Packing List

1 x MPC103-845
1 x Adapter (MPC103-845-J)
1 x Power cord (MPC103-845-J)
1 x Phoenix connector (MPC103-845 DC)

Optional Accessories

Wi-Fi + Bluetooth kit

GOT5103W-845 half slim SSD kit SFP for GOT5103W-845-PCT-J

881251030AOE Panel mount kit

8812B1070AOE Wall mount kit

881251203AOE RFID kit

E226171119 Stand Kit

Optional EOS Installation

WES 7

WE8S (64-bit)

Optional OS Installation

Windows® 7

Windows® 8.1 (64-bit)

Windows® 10



▲ AC power adapter
(for MPC103-845-J)

Dimensions

