



PLUS2

Panel printer

- High print quality (200 DPI)
- Paper width: 58mm
- Paper weight: 55-70gr/mq
- Paper roll dimension Ø 50mm
- Power supply: 4-7.5Vdc (9-48 Vdc with optional board)
- 4MB internal flash memory for logos and fonts
- Interfaces: RS232/TTL (selectable with lever switch), mini USB
- Barcodes: 1D and 2D (QRCODE)
- International fonts on-board: any language available
- Sensors: head temperature, paper presence, cover open (optional)
- UL, CE, FCC approved
- The ideal solution for tough environments: from -20 up to +70 degrees

CHARACTERISTICS

- **Energy-efficient** functionality to reduce consumption
- RGB status LED
- FEED button
- ECO MODE



With only one model of printer you can print on "linerless" adhesive paper or standard thermal paper, allowing to meet different needs and applications

APPLICATIONS

- Workshop equipment
- Medical equipment
- PC panel and control systems
- Weighing instruments: industrial, portable
- Fire detection systems
- Sterilization equipment
- Taximeters
- Truck tachographs
- Access control
- Measurement devices: durometers, electrical devices, etc...

AVAILABLE VERSIONS

- RS232/TTL and mini USB
- Mechanical version (without electronic board)

ACCESSORIES

- Extended range module (9-48 Vdc)

What is in the box:

- Device, fixing clips

TECHNICAL SHEET

| | |
|------------------------|---|
| Printing Method | Thermal |
| Number of dots | 8 dots/mm |
| Columns | 24, 32, 40, 42 |
| Resolution | 203 DPI |
| Printing (mm/sec) | max 50mm/sec (in absence of energy-efficient functionality) |
| Character set | European, International, Portuguese and Nordic, Chinese (GB18030), Katakana, Arabic, Greek, Turkish, Hebrew, and Cyrillic |
| Supported Barcode | 1D and 2D (QR CODE) |
| Paper width | 58 mm |
| Paper weight | from 55 to 70 g/m ² |
| Roll Dimension | Ø 50mm |
| Sensors | Head temperature, paper presence, cover open (optional) |
| Emulation | Escape Command Compatibility, PlusII compatibility |
| Interfaces | RS232/TTL, mini USB |
| Data Buffer | 16Kb |
| Flash Memory | 4MB (+768 Kb internal) |
| RAM Memory | 128Kb internal + 8MB external |
| Graphic Memory | 4MB internal flash memory for logos and fonts |
| Drivers | Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); Android™ |
| Software Tools | PrinterSet, CustomPowerTool, Custom Windows API |
| Power supply | 4-7.5 Vdc (9-48 Vdc with optional board) |
| Operating temperature | -20 a +70 |
| Marks | UL, CE, FCC |
| Dimensions | 56.9 (L) x 85 (H) x 85 (W) mm |
| Weight | 145gr |

MODELS



915CW180400322

PRINTER PLUS2 RX65 USB RS232
TTL



915CW180265333

PRINTER PLUS2 RX65 USB RS232
TTL MOV

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 19 February 2024